

(12) United States Patent

Tokuo et al.

US 9,410,543 B2 (10) Patent No.:

(45) Date of Patent: Aug. 9, 2016

(54) PUMP FOR LIQUID CHROMATOGRAPH, AND LIQUID CHROMATOGRAPH

(75) Inventors: **Kenichiro Tokuo**, Hitachinaka (JP);

Kenji Hiraku, Kasumigaura (JP); Hironori Kaji, Hitachinaka (JP); Daisuke Akieda, Hitachinaka (JP); Kimihiko Ishii, Hitachinaka (JP); Naoya

Yasuhara, Hitachinaka (JP)

Assignee: HITACHI HIGH-TECHNOLOGIES CORPORATION, Tokyo (JP)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 605 days.

(21) Appl. No.: 13/808,660

(22) PCT Filed: Jul. 20, 2011

(86) PCT No.: PCT/JP2011/066421

§ 371 (c)(1),

(2), (4) Date: Jan. 7, 2013

(87) PCT Pub. No.: WO2012/014741

PCT Pub. Date: Feb. 2, 2012

(65)**Prior Publication Data**

> US 2013/0104631 A1 May 2, 2013

(30)Foreign Application Priority Data

Jul. 29, 2010 (JP) 2010-169962

(51) Int. Cl.

F04B 17/03 (2006.01)F04B 13/00 (2006.01)

(Continued)

(52) U.S. Cl.

CPC F04B 17/03 (2013.01); F04B 13/00 (2013.01); F04B 23/06 (2013.01); F04B 49/06 (2013.01);

(Continued)

(58) Field of Classification Search

CPC F04B 13/00; F04B 23/06; F04B 49/065; F04B 17/03; F04B 49/06; F04B 49/08; F04B 2203/0202; F04B 2205/03; F04B 2205/05; G01N 30/02; G01N 30/34; G01N 2030/326

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

4,352,636 A * 10/1982 Patterson et al. 417/22 11/1989 Strohmeier et al. 4,883,409 A (Continued)

FOREIGN PATENT DOCUMENTS

DE 103 29 314 A1 5/2004 JP 1-104989 4/1989 (Continued)

OTHER PUBLICATIONS

JP Office Action of Appln. No. 2010-169962 dated Mar. 11, 2014 with English translation.

(Continued)

Primary Examiner — Hezron E Williams Assistant Examiner — Marrit Eyassu

(74) Attorney, Agent, or Firm — Baker Botts L.L.P.

(57)ABSTRACT

A pump controller causes a first plunger pump and a second plunger pump connected in series or in parallel to perform intake and compression actions alternately at substantially constant cycles, sets a pressurizing chamber of one of the plunger pumps to a state of a higher pressure than the pressurizing chamber of the other plunger pump, and performs flow rate control by adjusting lift amounts of the first plunger and the second plunger. Thus, it is possible to provide a pump for liquid chromatograph, and a liquid chromatograph, which are capable of reducing pulsations even when an ejection flow rate is changed.

17 Claims, 12 Drawing Sheets

